

Article number: 00 802 08 99

## Shower panel LINUS DP-SC-T

### Mixed water, ThermoProtect thermostat

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Manual actuation with automatic closing. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

#### Scope of delivery


- Self-closing exposed shower panel
  - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
  - SC self-closing button
  - Self-closing cartridge SC II
  - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
  - 2 backflow preventers (EN 1717: EB-type)
  - 2 pre-filters
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

#### Technical data

- Running time: 5 - 30 s (20 s )
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Material: Actuation Brass; Shower head Brass, conform to German drinking water regulations; Housing Aluminium; Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome; Shower head Chrome; Housing Brush anodised aluminium
- Dimensions: w 226 mm x h 1200 mm x d 115 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: Belgaqua

#### Delivery data

- Weight: 13,74 kg/Piece
- Packing unit: 1



#### Recommended associated articles

|                                |                          |
|--------------------------------|--------------------------|
| Soap tray shower panel LINUS   | Article no: 00 809 08 99 |
| Handle for thermostat EasyGrip | Article no: 29 192 06 99 |
| Sampling valve COMFORT Flex    | Article no: 01 823 00 99 |

#### For exposed connections from above

|  |                             |
|--|-----------------------------|
| Pipe set shower panel connection 500 mm          | Article no: 08 481 06 99 or |
| Pipe set shower panel connection 1000 mm         | Article no: 08 482 06 99 or |
| Connection cover shower panel LINUS 150 - 450 mm | Article no: 00 839 08 99 or |
| Connection cover shower panel LINUS 150 - 950 mm | Article no: 00 840 08 99 or |