

Article number: 00 820 08 99

Shower panel LINUS DP-C-T

Mixed water, ThermoProtect thermostat

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Triggering via CVD-Touch electronics with automatic closing. Optional battery or mains operation. Configurable via SCHELL Single Control SSC. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above. Solenoid valve for thermal disinfection integrated.

Scope of delivery


- Electronic self-closing exposed shower panel
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
 - Solenoid valve 12 V for carrying out thermal disinfection with key switch (without SWS, in accordance with DVGW worksheet W 551)
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
 - 6 V solenoid valve
 - 2 backflow preventers (EN 1717: EB-type)
 - 2 pre-filters
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Setting options via SSC
 - Actuation force (soft/medium/hard)
 - Manual programming (off/on)
 - Max. flow time (1-950 s)
 - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
 - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
 - Max. flow time (10-360 s in 10 program stages, factory setting 20 s)
 - Stagnation flush (off/20 s, every 24 h)
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C temporarily
- Material: Actuation Brass; Shower head Brass, conform to German drinking water regulations; Housing Aluminium; Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome; Shower head Chrome; Housing Brush anodised aluminium
- Dimensions: w 226 mm x h 1200 mm x d 115 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: Belgaqua

Delivery data

- Weight: 13,64 kg/Piece
- Packing unit: 1



Necessary associated articles

Concealed power supply unit 9 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 315 00 99 or

Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 582 00 99 or

Electrical junction box 9 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 583 00 99 or

Universal 6 V battery compartment Article no: 01 557 00 99 or

Together with mains adapter

Universal connection cable 5 m Article no: 01 570 00 99 or

Universal connection cable 10 m Article no: 01 571 00 99 or

For manual thermal disinfection

Thermal disinfection key switch Article no: 01 538 00 99

Concealed power supply unit 12 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 566 00 99 or

Mains adapter VDC, 100-240 VAC, 50-60 Hz Article no: 01 490 00 99 or

Electrical junction box 12 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 537 00 99 or

Recommended associated articles

Soap tray shower panel LINUS Article no: 00 809 08 99

Pipe set shower panel connection 500 mm Article no: 08 481 06 99 or

Pipe set shower panel connection 1000 mm Article no: 08 482 06 99 or

Connection cover shower panel LINUS 150 - 450 mm Article no: 00 839 08 99 or

Connection cover shower panel LINUS 150 - 950 mm Article no: 00 840 08 99 or

Handle for thermostat EasyGrip Article no: 29 192 06 99

Sampling valve COMFORT Flex Article no: 01 823 00 99

SSC Bluetooth® module Article no: 00 916 00 99

Not together with SWS and SSC Bluetooth module

CVD-protection filter Article no: 00 906 00 99