

Article number: 00 826 08 99

Shower panel LINUS DP-SC-M

Mixed water

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Manual actuation with automatic closing. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

Scope of delivery

- Self-closing exposed shower panel
 - SC self-closing button
 - Self-closing cartridge SC II
- LOW AEROSOL shower head, 20° ±6°, vandal-resistant
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Running time: 5 - 30 s (20 s)
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Material: Actuation Brass; Shower head Brass, conform to German drinking water regulations; Housing Aluminium; Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome; Shower head Chrome; Housing Brush anodised aluminium
- Dimensions: w 226 mm x h 1200 mm x d 115 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: Belgaqua

Delivery data

- Weight: 13,60 kg/Piece
- Packing unit: 1

Recommended associated articles

Soap tray shower panel LINUS
 Pipe set shower panel connection 500 mm
 Pipe set shower panel connection 1000 mm
 Connection cover shower panel LINUS 150 - 450 mm
 Connection cover shower panel LINUS 150 - 950 mm
 Sampling valve for shower heads

Article no: 00 809 08 99
 Article no: 08 481 06 99 or
 Article no: 08 482 06 99 or
 Article no: 00 839 08 99 or
 Article no: 00 840 08 99 or
 Article no: 01 817 00 99

