

Article number: 00 845 28 99

Shower panel LINUS Inox DP-SC-T Mixed water, ThermoProtect thermostat

Made from high-quality stainless steel (1.4404) material with a brushed finish. Integrated SCHELL shower fitting. Manual actuation with automatic closing. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above. Solenoid valve for thermal disinfection with SWS integrated.

Scope of delivery

- Self-closing exposed shower panel
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - SC self-closing button
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - Self-closing cartridge SC II
 - Solenoid valve 12 V for manual thermal disinfection (according to DVGW worksheet W 551)
- 2 backflow preventers (EN 1717: EB-type)
- 2 pre-filters
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data


- Running time: 5 - 30 s (20 s)
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C temporarily
- Material: Actuation Brass; Housing Stainless steel 1.4404; Piping Plastic, conform to German drinking water regulations; Waterpath Brass, conform to German drinking water regulations
- Surface: Actuation Chrome; Housing Brushed stainless steel
- Dimensions: w 240 mm x h 1200 mm x d 80 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: Belgaqua

Delivery data

- Weight: 12,80 kg/Piece
- Packing unit: 1

Necessary associated articles

Thermal disinfection key switch	Article no: 01 538 00 99
Concealed power supply unit 12 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 566 00 99 or
Mains adapter VDC, 100-240 VAC, 50-60 Hz	Article no: 01 490 00 99 or
Electrical junction box 12 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 537 00 99 or



Recommended associated articles

Soap tray shower panel LINUS inox	Article no: 00 850 28 99	
Pipe set shower panel connection 500 mm	Article no: 08 481 06 99	or
Pipe set shower panel connection 1000 mm	Article no: 08 482 06 99	or
Connection cover shower panel LINUS inox	Article no: 00 849 28 99	or
Connection cover shower panel LINUS inox	Article no: 00 851 28 99	or
Handle for thermostat EasyGrip	Article no: 29 192 06 99	
Sampling valve COMFORT Flex	Article no: 01 823 00 99	
Low aerosol shower head	Article no: 01 814 06 99	