

Article number: 02 186 06 99

Surface-mounted shower fitting MODUS MD-T with shower set Mixed water, ThermoProtect thermostat

Manual open/closed actuation.

Scope of delivery

- Open/closed exposed shower tap
 - Operating button open/close
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - IsoBody housing
 - Open/closed ceramic cartridge
- 2 backflow preventers (EN 1717: EB-type)
- Hand shower with anti-limescale knobs, 3-way adjustable
- Shower hose with anti-twist protection
- 2 S-connections and rosettes (depth-adjustable)
- Shower bar (stainless steel)
- Fastening material

Technical data

- Jet types: Soft, Vital, Power
- Max. operating temperature: 65 °C (for thermal disinfection 80 °C max. 10 min./day)
- Max. Outlet temperature: 38 - 43 °C adjustable
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome, Polished stainless steel
- length shower hose: 1500 mm
- length shower bar: 900 mm
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (bottom)

Delivery data

- Weight: 3,52 kg/Piece
- Packing unit: 1

Recommended associated articles

Article no: 29 239 00 99

or

Article no: 29 240 00 99

or

Hint

