

Article number: 01 608 06 99

Exposed shower tap VITUS VD -EH-M / o Mixed water

Manual open/closed actuation. Shower connection at top.

Scope of delivery




- Single-lever exposed shower tap
 - Single-lever mixer
 - Single-lever mixing ceramic cartridge with hot water and flow restrictor
 - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
- 2 backflow preventers (EN 1717: EB-type)
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (top)
- Certificates: PA-IX 38242/IB, Belgaqua
- Noise class: I
- Flow class: B

Delivery data

- Weight: 3,98 kg/Piece
- Packing unit: 1



Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
	Article no: 29 239 00 99	or
	Article no: 29 240 00 99	or

For concealed shower head connection

Outlet elbow VITUS DN 15	Article no: 25 667 06 99	or
Outlet elbow VITUS DN 15	Article no: 25 668 06 99	or
Shower head COMFORT Flex	Article no: 01 821 06 99	or
Low aerosol shower head	Article no: 01 814 06 99	or

For exposed shower head connection

Exposed pipe set VITUS	Article no: 25 666 06 99
Exposed shower head COMFORT	Article no: 01 846 06 99