

Article number: 01 612 06 99

# Exposed shower tap VITUS VD open/close-T / U

## Mixed water, ThermoProtect thermostat

Manual open/closed actuation. Shower connection at bottom.

### Scope of delivery




- Open/closed exposed shower tap
  - Operating button open/close
  - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
  - Open/closed ceramic cartridge
  - 2 backflow preventers (EN 1717: EB-type)
- 2 S-connections and rosettes (depth-adjustable)

### Technical data

- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (bottom)
- Certificates: PA-IX 38240/IB, Belgaqua
- Noise class: I
- Flow class: B

### Delivery data

- Weight: 4,21 kg/Piece
- Packing unit: 1



### Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Shower set 900	Article no: 29 207 06 99	or
Shower set 680	Article no: 29 208 06 99	or
	Article no: 29 239 00 99	or
	Article no: 29 240 00 99	or