

Article number: 01 196 00 99

## Urinal control COMPACT LC

Battery operation. Universal vandal-resistant flush control with corrosion-safe siphon with LC sensor. For all ceramic and stainless steel bowls. Plug + play plug connector, IP 54.



### Scope of delivery

- E-module
- Solenoid valve with adapter
- 6 V battery compartment, protection class IP65
- 4x AA alkaline battery 1.5 V
- Urinal siphon with LC sensor

### Technical data

- Functions
  - Stagnation flush (every 24 hours after last flush)
  - Automatic stadium program (reduced flush volume with high usage frequency >2 users/5 min)
  - Acoustic signal (when battery charge is low)
  - Odour trap flush (when water level is low)
  - Automatic flush stop (in case of blocked drain pipe)
- Setting options via Reedkontakt (accessories)
  - Flush programs (1 l, 2 l, hybrid flush)
  - Interval flush 5x (each flush 2 min contact time)
  - Cleaning flush 10 s
  - Cleaning stop 180 s
  - Diagnostics program

### Delivery data

- Weight: 0,60 kg/Piece
- Packing unit: 1

### Necessary associated articles

Urinal inlet connection DN 15 backflow preventer	Article no: 03 112 00 99 or
Urinal inlet connection DN 15	Article no: 03 105 00 99 or
Urinal module MONTUS	Article no: 03 089 00 99 or
Urinal module MONTUS	Article no: 03 075 00 99 or
Concealed urinal flush valve COMPACT II	Article no: 01 193 00 99 or

### Recommended associated articles

Sensor cable COMPACT LC Article no: 01 524 00 99

For program setting externally at the ceramics

COMPACT LC reed contact Article no: 01 529 00 99