

Article number: 02 476 06 99

Exposed urinal flush valve SCHELLOMAT Basic, DN 15

All-metal design with brass push button. Conform to DIN EN 12541.

Scope of delivery

- Exposed urinal flush valve
 - Self-closing cartridge with nozzle bore pre-filter
- Urinal internal connector
- Push rosette \varnothing 60 mm
- Flush pipe \varnothing 18 mm x 193 mm

Technical data

- Flow pressure: 0.8 - 5.0 bar
- Max. Resting pressure: 8 bar
- Flush flow: max. 0.3 l/s
- Flush volume adjustable: 1.0 - 6.0 l
- Material: Housing Brass; Parts in contact with water Brass, conform to German drinking water regulations, Plastic
- Surface: Chrome
- Connection: DN 15 G 1/2 AG
- Outlet: Internal connector \varnothing 43 mm (flush pipe \varnothing 18 mm)
- Certificates: PA-IX 9892/II, DIN-DVGW
- Noise class: II, at 100% flow

Delivery data

- Weight: 0,70 kg/Piece
- Packing unit: 1



Recommended associated articles

Flush pipe \varnothing 18 mm cranked	Article no: 50 223 06 99	or
Flush pipe \varnothing 18 mm cranked	Article no: 50 291 06 99	or
Urinal external connector	Article no: 27 820 06 99	
Urinal module MONTUS	Article no: 03 090 00 99	