



Article number: 01 947 00 99

Concealed Masterbox WBW-E-V Cold water/pre-mixed water

For LINUS W-E-V concealed wash basin taps. Electronic actuation. With sealed housing bushings and internal isolating valve.



Scope of delivery

- Masterbox
 - Roughing-in housing
 - Concealed wash basin tap with isolating valve
 - 6 V solenoid valve
 - Pre-filter
 - Backflow preventer (EN 1717: EB-type)
 - Mount for wall outlet
- Flushing nozzle
- Flush-mounted cap

Technical data

- Flow at 3 bar: 15 l/min
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Plastic; Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Dimensions: w 149 mm x h 138 mm x d 140 mm
- Installation depth: 100 - 124 mm
- Connection: G 1/2 IG
- Certificates: Belgaqua

Delivery data

- Weight: 1,98 kg/Piece
- Packing unit: 1

Necessary associated articles

Concealed wash basin tap LINUS W-E-V	Article no: 01 938 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 939 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 938 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 939 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 941 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 942 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 941 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 942 28 99	or

For building sealing according to DIN 18534

Expansion sleeve Article no: 00 919 00 99

Recommended associated articles

Wash basin module MONTUS Article no: 03 088 00 99