

Article number: 01 625 06 99

Exposed wash basin tap VITUS VW-E-T Mixed water, ThermoProtect thermostat

Infrared sensor-controlled. Battery operation. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC.

Scope of delivery



- Infrared sensor exposed wash basin tap
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - Infrared sensor electronics, programmable
 - 6 V solenoid valve with pre-filter
 - 2 backflow preventers (EN 1717: EB-type)
 - Pivoting outlet (lockable) with flow regulator
 - 6 V battery compartment (integrated)
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Setting options via SWS SSC
 - Programming via short range reflex (off/on)
 - Max. flow time (1-600 s)
 - Stagnation flush (off/5-600 s, every 1-240 h after last flush/every 1-240 h)
 - Continuous flush for thermal disinfection (off/15-600 s)
 - Duration of flow (off/15-600 s)
 - Energy saving mode (off/1-254 h after last flush)
 - Cleaning stop (off/60-360 s)
- Setting options via short range reflex
 - Max. flow time (4-240 s, 12 program stages)
 - Stagnation flush (off/30 s, every 24 h after last flush/every 24 h)
 - Cleaning stop (off/60 s)
- Flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Outlet Brass, conform to German drinking water regulations; Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 210 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: PA-IX 38235/IO, Belgaqua, WRAS applied
- Noise class: I
- Flow class: O

Delivery data

- Weight: 5,08 kg/Piece
- Packing unit: 1



Recommended associated articles

S-connecting with isolating valve
For parametrisation with Single Control SSC

Article no: 23 775 00 99

SSC Bluetooth® module VITUS	Article no: 00 917 00 99 or
<u>For networking with SWS water management system</u>	
SWS Server	Article no: 00 500 00 99
SWS Bus extender wireless BE-F VITUS	Article no: 00 507 00 99
<u>For thermal disinfection only with 01 625 06 99; 01 635 06 99; 01 645 06 99</u>	
Solenoid valve thermal disinfection SWS VITUS	Article no: 01 442 00 99