




Article number: 01 634 06 99

## Exposed wash basin tap VITUS VW-C-T Mixed water, ThermoProtect thermostat

Triggering via CVD-Touch electronics with automatic closing. Battery operation. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC.



### Scope of delivery

- Electronic self-closing exposed wash basin tap
  - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
  - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
  - 6 V solenoid valve with pre-filter
  - 2 backflow preventers (EN 1717: EB-type)
  - Pivoting outlet (lockable) with flow regulator
  - 6 V battery compartment (integrated)
- 2 S-connections and rosettes (depth-adjustable)

### Technical data

- Setting options via SWS SSC
  - Actuation force (soft/medium/hard)
  - Manual programming (off/on)
  - Max. flow time (1-950 s)
  - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
  - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
  - Max. flow time (4-120 s, 10 program stages)
  - Stagnation flush (off/20 s, every 24 h)
- Flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Outlet Brass, conform to German drinking water regulations; Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 270 mm
- Connection: 2x DN 15 G 1/2 AG
- Certificates: PA-IX 28575/IO, Belgaqua
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 5,20 kg/Piece
- Packing unit: 1

### Recommended associated articles

S-connecting with isolating valve

Article no: 23 775 00 99

Wash basin outlet valve OPEN

Article no: 02 002 06 99 or

Wash basin outlet valve PUSH OPEN

Article no: 02 000 06 99 or

For parametrisation with Single Control SSC

SSC Bluetooth® module VITUS	Article no: 00 917 00 99
<u>For networking with SWS water management system</u>	
SWS Server	Article no: 00 500 00 99
SWS Bus extender wireless BE-F VITUS	Article no: 00 507 00 99
<u>For thermal disinfection only with 01 624 06 99; 01 634 06 99; 01 644 06 99</u>	
Solenoid valve thermal disinfection SWS VITUS	Article no: 01 442 00 99