

Article number: 00 207 06 99

Electronic wash basin tap CELIS E HD-K - high-pressure cold water/pre-mixed water

Infrared sensor-controlled. Excluding power supply. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC. Intended for power supply via SCHELL water management system SWS or central power supply unit.



Scope of delivery

- Infrared sensor single-hole tap
 - Infrared sensor electronics, programmable
 - 6 V solenoid valve with pre-filter
 - Flow regulator
 - Connection cable, 250 mm, with 3-pin plug connector, protection class IP65
- Flexible Clean-Fix S connection hose, G 3/8 IG x 380 mm, with pre-filter
- Fastening material for wash basin installation

Technical data

- Setting options via SWS SSC
 - Sensor range (short/medium/long)
 - Programming via short range reflex (off/on)
 - Max. flow time (1-360 s)
 - Follow-up time (0.6-60 s)
 - Stagnation flush (off/5-600 s, every 1-240 h after last flush/every 1-240 h)
 - Continuous flush for thermal disinfection, with anti-scalding protection (off/15-600 s)
 - Duration of flow (off/15-600 s)
 - Energy saving mode (off/1-254 h after last flush)
 - Cleaning stop (off/60-360 s)
- Setting options via short range reflex
 - Sensor range (short/medium/long)
 - Stagnation flush (off/30 s, every 24 h after last flush/every 24 h)
 - Continuous flush for thermal disinfection, with anti-scalding protection (off/300 s/120 s)
 - Cleaning stop (off/60 s)
- Flow: max. 5 l/min pressure independent
- Flow: 1.0 - 5.0 l/min
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: G 3/8 IG
- Certificates: P-IX 19116/IZ
- Noise class: I
- Flow class: Z

Delivery data

- Weight: 1,82 kg/Piece
- Packing unit: 1

Necessary associated articles

| | |
|-----------------------------|--------------------------|
| SWS Server | Article no: 00 500 00 99 |
| SWS Bus mains adapter | Article no: 00 505 00 99 |
| SWS Bus extender cable BE-K | Article no: 00 501 00 99 |

Recommended associated articles

| | |
|--|-----------------------------|
| Angle valve with regulating function COMFORT with filter | Article no: 05 430 06 99 |
| Wash basin outlet valve OPEN | Article no: 02 002 06 99 or |
| Wash basin outlet valve PUSH OPEN | Article no: 02 000 06 99 or |

Optional power supply via collective mains adapter

| | |
|--|-----------------------------|
| Concealed power supply unit 9 VDC, 100 - 240 VAC, 50 - 60 Hz | Article no: 01 315 00 99 or |
| Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - 60 Hz | Article no: 01 582 00 99 or |
| Electrical junction box 9 VDC, 100 - 240 VAC, 50 - 60 Hz | Article no: 01 583 00 99 or |