


Article number: 02 176 06 99

## Electronic wash basin tap MODUS E HD-K - high-pressure cold water/pre-mixed water

Infrared sensor-controlled. Battery operation.



### Scope of delivery

- Infrared sensor single-hole tap
  - Infrared sensor electronics, programmable
  - 6 V solenoid valve with pre-filter
  - Flow regulator
  - Connection cable, 200 mm, with 2-pin plug, protection class IP65
  - Flexible connection hose, G 3/8 IG x 450 mm, with pre-filter
- 6 V battery compartment, protection class IP65
- 4x AA alkaline battery 1.5 V
- Fastening material for wash basin installation

### Technical data

- Setting options via short range reflex
  - Sensor range area (approx. 2-17 cm)
  - Stagnation flush (off/duration of flow 30 s, 24 h after last use)
  - Cleaning stop (off/120 s)
- Flow: max. 3 l/min pressure independent
- Flow pressure: 0.5 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (temporarily, e.g. for thermal disinfection)
- Material: DZR brass
- Surface: Chrome
- Connection: G 1/2 IG
- Certificates: P-IX 29853/IO, dr, Watermark, WELS
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 1,73 kg/Piece
- Packing unit: 1

### Recommended associated articles

Angle valve with regulating function COMFORT with filter	Article no: 05 430 06 99
Flow regulator set LEED 1.3 l	Article no: 28 931 06 99 or
Wash basin outlet valve OPEN	Article no: 02 002 06 99 or
Wash basin outlet valve PUSH OPEN	Article no: 02 000 06 99 or