

Article number: 00 290 06 99

# Electronic wash basin tap PURIS E<sup>2</sup> HD-M - high-pressure mixed water

Contactless, sensor-controlled tap with innovative ToF technology. Insensitive against reflective materials such as mirrors, saftety vests, etc. With integrated Bluetooth® interface. Configurable via SCHELL app. Suitable for networking with the SCHELL SWS water management system. Battery operation. With extended outlet 134 mm.

# Scope of delivery

- Time-of-flight sensor single-hole tap
  - Temperature controller with hot water restrictor
  - Time-of-flight sensor electronics (ToF) with automatic adjustment of the sensor range
  - 6 V axial solenoid valve with pre-filter
  - Recessed aerator (theft-protected)
  - Connection cable, 220 mm, with 3-pin plug connector, protection class IP65
- 6 V battery compartment (integrated)
- 4x AAA alkaline battery 1.5 V
- 2 flexible Clean-Fix S connection hoses, G 3/8 IG x 410 mm, with integrated backflow preventer (EN 1717: EB-type) and pre-filter
- Fastening material for wash basin installation

#### **Technical data**

- Setting options via SCHELL App
  - Quick configuration via preset operating modes (save electricity / save water / comfort)
  - Individual settings in expert mode (sensor range, sensor measuring interval, person detection, max. runtime, run-on time)
  - Stagnation flush (off / at intervals / smart demand-based flush taking usage into account / at fixed times [day(s), time])
  - Continuous flush for thermal disinfection, triggering via app (3 10 min)
  - Continuous flow, triggering via app (15 600 s)
  - Cleaning stop, triggering via app or proximity reflex (off / 60 360 s)
- Flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Material: Housing Brass
- Surface: Chrome
- Connection: 2x G 3/8 IG
- Certificates: PA-IX 10332/IO, DVGW applied
- Noise class: IFlow class: O


## **Delivery data**

Weight: 1,60 kg/PiecePacking unit: 1

## **Recommended associated articles**

Angle valve thermostat Article no: 09 414 06 99







Angle valve with regulating function COMFORT with Article no: 05 430 06 99

filter

Wash basin outlet valve OPEN Article no: 02 002 06 99 or Wash basin outlet valve PUSH OPEN Article no: 02 000 06 99 or

For mains-supplied fittings

Extension cable Article no: 51 010 00 99 or Extension cable Article no: 51 023 00 99 or

#### Hint

• Previous Electronic washbasin tap PURIS E 01 226 06 99 expected to be available until II. quarter 2025.